What Goes First On The Faucet?

An Installation Guide

Mister Landscaper offers a variety of solutions when it comes to connecting a Drip & Micro Irritation system to an outdoor faucet. Here is a simple guide with options we suggest to help keep things in the correct order:

1) Check your outdoor faucet to make sure there is an attached Brass Anti-Siphon Vacuum Breaker that's designed to prevent the backflow of fluids back into the potable/drinking water system. Note: This Brass Anti-Siphon device is NOT needed if your Faucet has a built in Anti-Siphon like the one shown here.



- 3) Electronic Water Timer (MLWT-1ZONE) is used to automate your Drip & Micro Irrigation System
- 4) Pressure Regulators: When using Drippers, we
 - highly suggest using our 25 PSI Regulator (MLD-25PR) & when using our Micro Sprays with a water pressure over 50 PSI, use our 50 PSI Regulator (MLA-58)
- 5) 150 Mesh Filter (MLFF-41) is suggested for Drippers or when using our products with "Well" water
- 6) 1/2" Poly Faucet Fitting (MLF-33), which connects to the 1/2" Poly Tubing mainline OR the 1/4" Faucet Adapter (MLA-FAS), which connects to the 1/4" Vinyl Tubing mainline

Hose Thread x 1/2" Poly 1/2" Poly Tubing as the mainline

150 Mesh Screen Filter MLFF-41

3

5

Outdoor Faucet

Brass Anti-Siphon

backflow preventer

Metal "Y" Fitting

Timer

MLWT-1ZONE

Pressure

MLA-58

Regulator

MLD-25PR or

MLF-33

Hose Thread x 1/4" Barb MLA-FAS 1/4" Vinyl Tubing as the mainline